



The best choice for corrugated sheets and cardboard



**The best modular belt systems for
the corrugated sheet and cardboard industry –**

**plastic modular belt systems
from uni-chains**

The perfect for the Corb

Modern corrugated plant

A corrugated packaging production plant can be divided into 4 different sections:

- The corrugated production plant
- The product transfer stations
- Finishing machines
- Stock of finished goods incl. packing and shipping

Modern corrugator machines operate at high speeds. Corrugated sheets can be produced at a feed rate of 400 m/min (1310 ft/min) placing a high demand on downstream conveyor and handling systems. On a corrugator outfeed corrugated sheets are automatically cut to length and stacked ready for further processing.


In state-of-the-art plants, the transport of these stacks of cardboard sheets which can be up to 2 m (6.6 ft) high is made without pallets and in fully-automated, computer-controlled systems. These control systems track and manage complex order schedules automatically and balance workflow around the plant.

Stacks of products are moved across the plant by transfer cars. These are mobile conveyors which connect the different plant sections automatically.


Storage areas from several 100 m² (1100 ft²) to more than 2000 m² (21500 ft²) are likewise equipped with automatic conveyors to ensure a quick and direct handling of orders (work in progress) between corrugator and finishing operations. The storage area acts as a buffer to balance corrugator and final production processes.

Finishing or converting machines complete the production process, with operations such as die-cutting, printing, folding and gluing.

Finally, products are automatically strapped and palletised ready for despatch.



Best solutions for the board industry



Typical Plant Layout

- A. Corrugator Machine
- B. Downstacker
- C. Corrugator Take Off
- D. Transfer Car
- E. WIP Storage
- F. Finishing Machines
- G. Strapping and Palletising



Transfer Car



Downstacker



Corrugator Take Off



WIP Storage

Problems in traditional conveyor systems

Large parts of the corrugated sheet and cardboard industry still work with the traditional roller tracks, belt over roller and roller-slat chain conveyor combinations.

These can all exhibit problems such as: stack creep – resulting in an ‘elephant’s foot’ stack profile, stack instability, snagging and toppling of stacks. Also when running on traditional handling systems lower layers in stacks frequently have to be written off because of contact pressure points and running marks.


With these traditional systems there can be vast production losses and wasted goods that cannot be reused.

Added to this are the lengthy production standstills needed to re-erect toppled stacks.

Not forgetting the consequences of staff accidents, where personnel try to stand or walk across static or moving roller conveyors.




....Lower sheet creep



Demands from corrugated production lines

- Steady running for a secure stack conveying
- Stack height minimum three times stack width and possibly much higher
- Secure conveying of the smallest stacks
- No deterioration of the lower sheets, no impact on sheet quality
- No sheet creep
- Conveying of all existing qualities with weights up to 1200 kg/m² (245 lb/ft²)
- High conveying and storage capacity
- Bi-Directional travel
- Speeds up to 40 m/min (130 ft/min) smooth run, soft start and stop
- High operational safety, long service life, minimum maintenance costs
- Simple quick installation
- Easy to clean contact surfaces



Plant for 8 m wide stacks




Sheet feeder plant



Stack turning



WIP Storage



Right angle station



Turntable

Conveyor solutions from uni-chains

uni-chains offers solutions from corrugator take-off to final product despatch.

- If you would like to lower the costs caused by conveying damage
- If you want to ensure flatness of the support of your sheets
- If you want to reduce possibilities of the bottom sheets creeping out of the stack
- If you want to reduce the waste of the bottom sheets
- If narrow sheet stacks tilt
- If you want to increase safety for personnel walking across conveyors

Talk to uni-chains about plastic modular belt solutions.

Advantages of uni modular belt systems

Strong, reliable, but simple conveyor medium.

Assembled from hinged modules in brick-layed pattern.

Can be made in many different widths, lengths, pitches and surface types.

Suitable for heavy-duty applications with load of up to 1200 kg/m² (245 lb/ft²) already in operation.

Smooth-running speeds up to 40 m/min (130 ft/min) with soft start and stop.

Long service lifetime. Low maintenance.

Clean flat surfaces for improved product quality.

The best result

With uni-chains you will have the complete solution to all your internal conveying problems - from stacker to loading, conveyance to and from the various feed units and the intermediate warehouse, and the final conveyance from the production plant.

The systems can also handle corner transitions with 90° direction changes with maximum precision.


Stacks are turned and positioned accurately for further processing. Transfer trucks and mobile conveyors provide smooth transfer between individual conveyor sections. And if needed the stack flows can be easily sent in any direction using a rotating disk. All using plastic modular belt systems from uni-chains.

All to improve productivity, safety and efficiency in the corrugated board industry.

Belt Specifications

uni QNB

uni QNB has become very popular in the corrugated and cardboard industry. Its flat, solid, smooth and even surface increases safety for the personnel and eliminates stack tippage, sheet warp, and pressure damage or marking on the lower sheets.



Standard materials:

POM-SLF **PP**


Standard pin materials:
PP, white and PA6.6, blue or red

Pitch: 25.4 mm (1.00 inch)

Surface opening:

Closed

Patent pending




Permissible Tensile Strength

Belt material	POM				PP			
	PA6.6		PP		PA6.6		PP	
Pin material	N/m	lbf/ft	N/m	lbf/ft	N/m	lbf/ft	N/m	lbf/ft
uni QNB	35000	2400	35000	2400	20000	1370	20000	1370

	mm	inch
E	5.2	0.20
L	4.4	0.17
P	25.4	1.00
T	8.8	0.35

uni M-QNB

uni M-QNB provides good support for the transport of products in the corrugated industry, where there is a need for a tight transfer capability to eliminate sheet creep.



Standard materials:

POM-SLF **PP** **PP**


Standard pin materials:
PA6.6, red and natural

Pitch: 12.7 mm (0.50 inch)

Surface opening:

Closed

Patent pending



Permissible Tensile Strength

Belt material	POM		PP	
	PA6.6		PA6.6	
Pin material	N/m	lbf/ft	N/m	lbf/ft
uni M-QNB	19000	1300	13000	900

	mm	inch
E	5.2	0.20
L	4.4	0.17
P	12.7	0.50
T	8.8	0.35

Quality technology

The correct engagement of belt and sprocket is essential to the quality of conveyance. With uni-chains products you are always guaranteed that the belt and sprocket are ideally designed to compliment each other - providing constant safe and smooth conveying.

Sprockets for uni QNB

The standard material is Polyamide.

The standard sprocket sizes for uni QNB are 10, 12, 15, 18 and 19 teeth. Please contact uni-chains for further information.

The width of the sprockets is 25 mm (1.0 inch), and the tooth width is 10 mm (0.4 inch).

Sprockets for uni M-QNB

The standard material is Polyamide.

The sprocket standard sizes for uni M-QNB are 10, 19, 28 and 38 teeth, with round and square bore.

Please contact uni-chains for further information.

The width of the sprockets is 20 mm (0.8 inch), and the tooth width is 7 mm (0.3 inch).



uni QNB sprocket



uni M-QNB sprocket

Global Sales Organization, www.unichains.com



Head Office, Denmark

uni-chains A/S
Hjulmagervej 21, DK-7100 Vejle
Tel: +45 75 72 31 00,
Fax: +45 75 72 33 48,
e-mail: admin@unichains.dk
www.unichains.com



Germany

uni-chains Deutschland GmbH
Postfach 2129, DE-48411 Rheine
Münsterstrasse 57a, DE-48431 Rheine
Tel: 05971-91437-0,
Fax: 05971-915475,
e-mail: admin@unichains.de



Great Britain

uni-chains A/S
Coombs Wood Business Park
Coombs Wood Way
Halesowen
West Midlands
B62 8BH
Tel: 0121-559-0377,
Fax: 0121-559-0373,
e-mail: admin@unichains.co.uk



Ireland

uni-chains Ireland Ltd.
12, The Park
Liffey Hall, Newbridge
Co. Kildare, Ireland
Tel: 00-353-87-2633401,
Fax: 00-353-45-437514,
e-mail: unichains@eircom.net



Italy

uni-chains Italia s.r.l.
Via Napoli, 10-10a
42100 Reggio Emilia
Tel: 0522 • 922470,
Fax: 0522 • 922508,
e-mail: unichains@unichains.it



Singapore

uni conveyor chains Asia Pte Ltd.
No. 6 Ubi Road 1
05-03 Wintech Centre
Singapore 408726
Tel: 67498513/4,
Fax: 67498515,
e-mail: unichains@pacific.net.sg



USA

uni-chains Manufacturing Inc.
500 Brentwood Drive,
Reading, PA 19611, USA
Tel: (610)-372-1800, Tel: (800)-937-2864
Fax: (610)-372-3590
e-mail: sales@unichains.com



Argentina
011 4717-5151



Australia
Belts: Heat & Control Pty. Ltd. (07) 3877 6333
Chains: Renold Australia Pty. Ltd. (03) 9262 3333



Austria
(01) 292 1071



Belarus
017 280 45 78



Belgium
(09) 243 73 73



Brazil
(11) 6402-3022



Canada
(800)-937-2864
Ringball: (905) 826-1100



Chile
026 963126



Colombia
4 262 03 23



Czech Republic
00420 272 706 052



Egypt
02 451 07 93




Estonia
06 684 400



Finland
89-852661



France
 0810442900
Faber (03) 24 27 03 29



Greece
(0210) 4111841



Hungary
13 20 64 44



Iceland
517-2220



India
080 2242588



Iran
021-8722237



Israel
03-9415150



Japan
066 561 2014



Latvia
07248036



Lithuania
(05) 239 25 25



Mexico
055 5341 8131



Netherlands
074-255 36 36



New Zealand
Belts: Heat & Control Ltd. 09 274 4182
Chains: Renold New Zealand Ltd. 09 828 5018



Nigeria
(084) 483525



Norway
2220 2699



Poland
(022) 664 3887



Portugal
(02) 29478090



Romania
021-221 9640



Russia
Moscow branches:
Megadrive Ltd. 095 346-24-10
Polymer MK Ltd. 095 257-44-19
St. Peterburg branch:
Megadrive-Spb Ltd. 812 389-13-38



Slovakia
00420 272 706 052



South Africa
011-7479500



South Korea
031-479-5100



Spain
(91) 507 28 38



Sweden
040-18 10 00



Switzerland
Plüss (01) 824 88 00
Renold (01) 824 84 84



Taiwan
02 22182201



Turkey
0212 657 89 46



UAE
04 299 4828



Ukraine
044 467-57-35