




Bakery Innovations

The best result...

uni-chains provides the complete solution to all of your conveyance needs/problems from dough conveyors to pallet handling. We have developed products that will exceed your expectations whether you need a cleanable belt, a wear resistant chain or a belt to convey a full load of pallets.



uni Light CR Belt



uni SSB 32%
Open Belt



uni Flex SNB-W Belt

Let uni-chains help you increase efficiency and reduce production costs at the same time.

Advantages of uni Conveyor Chains:

- Less downtime due to higher tensile strength
- High temperature chains
- Longer chain life due to wear resistant materials
- Quick and easy installation with unique locking system
- Safety chains reduce risk of clothes or fingers being caught/trapped
- Increased friction with molded rubber inserts
- F.D.A. approved materials and U.S.D.A. accepted products (see www.unichains.com for details)


Advantages of uni Modular Plastic Belt:

- High temperature belts
- Tighter transfer possible with the **new** 25.4 mm pitch uni S-MPB Single Link™
- Quick and easy assembly/disassembly with the new Lockpin
- High tensile strength with reinforced side flexing belts
- Easy to clean Roller Top belt for crate/box accumulation
- Special wear resistant materials increase your belt life
- Low noise belts for pan handling
- F.D.A. approved materials and U.S.D.A. accepted products (see www.unichains.com for details)

www.unichains.com




Modular Plastic Belt and Conveyor Chain Solutions for the Bakery Industry




uni M-SNB M2

Standard materials:
 POM-D PP PE




uni M-QNB C

Standard materials:
 POM-SLF PP PP




uni Light C

Standard materials:
 POM-LF PP PP PE PA-6




uni SNB M2

Standard materials:
 POM-D PP PE



uni Flex SNB-CR
Tight radius

Standard materials:
 POM-D POM-D PP PP




uni Flex SNB-WT
Integral molded edge wearpart

Standard materials:
 POM-D POM-D PP PP PA6.6 PA6.6



uni QNB with rubber

Standard material:
 PP Rubber material:
 Thermolast K, black



uni CNB C

Standard materials:
 POM-D PP PP PE




uni S-MPB Single Link™

Standard materials:
 POM-D PP PE PA6.6




uni SSB C

Standard material:
 PP




uni MPB C

Standard materials:
 POM-I POM-I PP PP PE-I PE-I



uni MPB
Standard Product Support S-types

Standard materials:
 POM-D POM-D PP-I PP-I PE PE



uni MPB RO

Standard materials:
 POM-I POM-I
 Roller: POM-I



uni XLB C

Standard material:
 POM-NL




uni 802/810

Standard materials:
 SS304 SS430 S1045



uni 881

Standard materials:
 SS304 SS430 S1045



uni 820

Standard materials:
 POM-D POM-D POM-LF POM-SLF



uni 880/882

Standard materials:
 POM-D POM-D POM-LF POM-SLF

Application Guidelines

D/LF/SLF/NL-POM • PP-Polypropylene • PE-Polyethylene

Belt/Chain Style	Belt/Chain Pitch	Oven Infeed and Takeaway	Cooling lines	Freezing Lines	General Conveyance	Raw Dough Handling	Conditioning	Laminating	Pan Handling	Proofer	Pan Washing	Metal Detectors	Packing Lines	Tray Conveyance	Box Handling	Pallet Handling
uni M-SNB M2	0.50 in.		PP/D	PE/D	PP		PP			PP		PE	PP/D	PP/D		
uni M-QNB C	0.50 in.				PP			PP					PP/SLF	PP/SLF		
uni Light C/CR/22%	0.75 in.		D/LF		PP/D	PE	PP	PE/PP		PP		PE	PP/D	PP/D		
uni SNB M2	1.00 in.		D	PE/D	PP/D		PP		D	PP	PP/D	PE	PP/D	PP/D	D	
uni Flex SNB-CR	1.00 in.		PP/D		PP/D				D	PP/D				PP/D	D	
uni Flex SNB-W/WO/WT	1.00 in.	D			PP/D				D	PP/D				PP/D	D	
uni QNB with rubber	1.00 in.								PP					PP	PP	
uni CNB C/18%/22%	1.00 in.		PP/D		PP/D	PE	PP	PE/PP		PP		PE	PP/D	PP/D		
uni S-MPB Single Link™	1.00 in.				PP/D	PE		PE/PP				PE	PP/D	PP/D		
uni SSB C/29%/32%	1.50 in.	LF	LF		PP/LF		PP		LF	PP	PP/LF		PP/D	PP/D	LF	
uni MPB C/18%/20%	2.00 in.		PP/D	PE/D	PP/D	PE	PP	PE/PP	PP/D		PP/D		PP/D		D	
uni MPB RO	2.00 in.								D				D	D	D	
uni XLB C	2.50 in.															NL
uni 802/810/881	1.50 in.	S			S				S							
uni 820/880/882	1.50 in.				LF				LF		LF		LF	LF	LF	