



## Beverage Innovations

The best result...

uni-chains provides the complete solution to all of your conveyance needs/problems from depalletizer to palletizer. We have developed products that will exceed your expectations whether you need a high speed belt, a wear resistant chain or a belt to convey a full load of pallets.



uni SS 881 TAB Chain



uni Gripper Chain



uni Flex SNB Belt

*Let uni-chains help you increase efficiency and reduce production costs at the same time.*

### Advantages of uni Conveyor Chains:

- Less downtime due to higher tensile strength
- Longer chain life due to wear resistant materials
- Super low friction material for high speed applications
- Bevel edges reduce tippage with side transfer
- Increased friction with moulded rubber inserts
- Angled grippers allow for smoother transfer, reducing tippage/misaligning  
(see [www.unichains.com](http://www.unichains.com) for details)

### Advantages of uni Modular Plastic Belt:

- Conveyors are able to run dry with self-lubricating acetal modules
- Super Low Friction material reduces soap/water usage
- Quick and easy assembly/disassembly with the new Lockpin
- High tensile strength with reinforced side flexing belts
- Easy to clean Roller Top belt for crate/box accumulation
- Patented radius top surface reduces back line pressure and oxide build-up from cans
- Exceptionally flat surfaces for transferring motion-sensitive PET bottles  
(see [www.unichains.com](http://www.unichains.com) for details)

[www.unichains.com](http://www.unichains.com)



## Modular Plastic Belt and Conveyor Chain Solutions for the Beverage Industry

uni M-QNB C	uni M-QNB with rubber	uni Light C	uni Light Vacuum	uni SNB M2	uni SNB M2 Rib	uni Flex SNB-WT Integral molded edge wearpart
Standard materials: POM-SLF PP PP	Standard materials: POM-SLF PP PP	Standard materials: POM-LF PP PP PP PE PA-6	Molded to order	Standard materials: POM-D PP PE	Standard materials: POM-D PP PE	Standard materials: POM-D POM-D PP PP PA6.6 PA6.6
uni QNB C	uni QNB with rubber	uni SSB C	uni L-SNB Rib	uni OPB 4V 23% Rib	uni MPB PRR	uni XLB C
Standard materials: POM-SLF PP	Standard material: PP Rubber material: Thermolast K, black	Standard materials: POM-LF PP	Standard materials: POM-LF PP	Standard materials: PP PP	Standard material: Baselink: [POM-I] Rollers/Roller bed: PA6 [POM-I]	Standard material: POM-NL
uni 881	uni 805/815	uni 820	uni 880/882	uni Grip 1873-G3/G4	uni Grip 1873-D	Chains with molded Rubber Inserts
Standard materials: SS304 SS430 S1045	Standard materials: SS304 SS430 S1045	Standard materials: POM-D POM-D POM-LF POM-SLF	Standard materials: POM-D POM-D POM-LF POM-SLF	Standard materials: POM-D POM-LF	Standard materials: POM-D POM-LF	

## Application Guidelines

D/LF/SLF/NL-POM • PP-Polypropylene • SS-Stainless Steel

Belt/Chain Style	Belt/Chain Pitch	Depalletizer	Vacuum Conveyor	General Conveyance	Mass Handling	Accumulation Table	Rinser/Elevator	Single Filler/Combiner	Filler Lines	Capper Machine	Warmer/Cooler	Pasteurizer	Case Packer	Case Conveyor	Case Conveyor Inline/Decline	Case/Box Accumulation	Palletizer	Pallet Handling
uni M-QNB C	0.50 in.	SLF		SLF	SLF	SLF												
uni M-QNB with rubber	0.50 in.														PP			
uni Light C	0.75 in.	LF		LF	LF					PP/LF							LF	
uni Light Vacuum	0.75 in.		LF															
uni SNB M2	1.00 in.	D		D	D	D		D	D									
uni SNB M2 Rib	1.00 in.	SLF				SLF					PP/SLF							
uni Flex SNB-W/WO/WT	1.00 in.			D	D									D	D	D		
uni QNB C	1.00 in.	SLF		SLF	SLF	SLF		SLF	SLF	PP/SLF			SLF	SLF			SLF	
uni QNB with rubber	1.00 in.														PP			
uni SSB C	1.50 in.			LF	LF	LF		LF	LF	PP/LF			LF	LF	LF	LF	LF	
uni L-SNB Rib	2.00 in.	PP/LF									PP	PP						
uni OPB 4V Rib 23%	2.00 in.										PP	PP						
uni MPB PRR	2.00 in.																D	
uni XLB C	2.50 in.	NL															NL	NL
uni 815/805	1.50 in.			SS	SS			SS	SS					SS	SS	SS		
uni 881/uni 881 Super Flex	1.50 in.			SS	SS			SS	SS					SS	SS	SS		
uni 820/831/821	1.50 in.		LF	LF	LF			LF	LF				LF	LF	LF			
uni 880/879/882	1.50 in.		LF	LF	LF			LF	LF				LF	LF	LF			
uni Grip 1873-G3/G4	0.75 in.																	
uni Grip 1873-D	0.75 in.																	