



Meat Innovations

The best result...

uni-chains provides the complete solution to all of your conveyance needs/problems from Offal Conveyors to cutting lines and pallet handling. We have developed products that will exceed your expectations whether you need a cleanable belt, a wear resistant chain or a belt to convey a full load of pallets.



uni MPB Single Link™



uni MPB Closed Belt



uni MPB Closed Belt

Let uni-chains help you increase efficiency and reduce production costs at the same time.

Advantages of uni Conveyor Chains:

- Less downtime due to higher tensile strength
- Longer chain life due to wear resistant materials
- Quick and easy installation with unique locking system
- Safety chains reduce risk of clothes or fingers being caught/trapped
- Increased friction with molded rubber inserts
- F.D.A. approved materials and U.S.D.A. accepted products (see www.unichains.com for details)


Advantages of uni Modular Plastic Belt:

- Easy to clean, Single Link™ *no brick lay*
- Strong and thick product supports allow more load without breakage
- Quick and easy assembly/disassembly with the new Lockpin
- High tensile strength with reinforced side flexing belts
- Easy to clean Roller Top belt for crate/box accumulation
- More load/longer conveyors with unique sprocket engagement
- Tighter transfer possible with the *new* 25.4 mm pitch uni S-MPB Single Link™
- F.D.A. approved materials and U.S.D.A. accepted products (see www.unichains.com for details)

www.unichains.com




Modular Plastic Belt and Conveyor Chain Solutions for the Meat Industry




uni M-QNB C

Standard materials:
 POM-SLF PP PP




uni SNB M2AC

Standard materials:
 POM-D PP



uni Flex SNB-CR
Tight radius

Standard materials:
 POM-D POM-D
 PP PP




uni Flex SNB-WT
Integral molded edge wearpart

Standard materials:
 POM-D POM-D
 PP PP PA6.6 PA6.6



uni QNB with rubber

Standard material:
 PP Rubber material:
 Thermolast K, black




uni CNB C

Standard materials:
 POM-D PE PP PP




uni S-MPB Single Link™

Standard materials:
 POM-D PP
 PE PA6.6




uni MPB C
uni MPB Single Link™

Standard materials:
 POM-I POM-I
 PP PP PE-I PE-I



uni MPB-GE

Standard material:
 POM-I




uni MPB RO

Standard materials:
 POM-I POM-I
 Roller: POM-I




uni MPB
Bent Product
Support

Standard materials:
 PP-I PE



uni MPB
Standard Product
Support S-types

Standard materials:
 POM-D POM-D
 PP-I PP-I PE PE




uni MPB
No Cling Product
Support NC-types

Standard materials:
 PP-I PP-I PE



uni XLB C

Standard material:
 POM-NL



uni 882 TAB/Safety Chain

Standard materials:
 POM-LF POM-SLF
 POM-D POM-D

Application Guidelines

SLF/LF/D/NL-POM • PP-Polypropylene • PE-Polyethylene

Belt/Chain Style	Belt/Chain Pitch	Evisceration Lines	Offal Conveyors	Cutting Lines	Deboning Lines	Fat/Trim Lines	Pacing Lines	Elevators/Incline Conveyors	Breading Conveyors	Shrink Wrap Conveyors	Tray Pack Lines	Box/Tote Handling	Box/Tote Incline/Decline Conveyors	Freezers Infeed/Outfeed	Spirals	Pallet Handling	General Conveyance Straight	General Conveyance Grip	General Conveyance Radius	Metal Detector
uni M-QNB C	0.50 in.									SLF	PP/SLF						SLF			
uni SNB M2AC	1.00 in.									D	D	D		PP/PE			D	PP		PE
uni Flex SNB-L/CR	1.00 in.									D	PP/D	PP/D		D	PP/D				PP/D	
uni Flex SNB-W/WO/WT	1.00 in.									D	PP/D	PP/D	D	D	D				PP/D	
uni QNB with rubber	1.00 in.							PP			PP	PP	PP					PP		
uni CNB C/18%/22%	1.00 in.	D							D								D			PE
uni S-MPB Single Link™	1.00 in.	D	D			D					D						D			
uni MPB C/MPB Single Link™	2.00 in.	PE/D	PE/D	D	D	PE/D	D	PE/D	PE/D	PE/D	D	D	D	PE/D			PE/D			PE
uni MPB-GE	2.00 in.		D					D										D		
uni MPB RO	2.00 in.										D	D								
uni XLB C	2.50 in.															NL				
uni 882 TAB/Safety Chain	1.50 in.										LF	LF	LF							